

2.5A Single-Phase GLass Passivated Bridge Rectifiers

Rectifier Reverse Voltage 50V to 1000V



MSB

Features

- Glass passivated junction
 - The plastic material used carries Underwriters Laboratory flammability recognition 94V-0
 - Suge overload ratings to 60 amperes peak
 - Ideal for printed circuit board application
 - High temperature soldering guaranteed 265°C/10 seconds at 5 lbs(2.3kg)tension

Mechanical Data


Case:Molded plastic

Terminals: Platde leads solderable per MIL-STD-750,
Method 2026

Polarity: Polarity symbols molded or Marked on body

Mounting Position: Any

Weight:0.007ounce,0.2 grams(approx)



Maximum Ratings & Thermal Characteristics

Rating at 25°C ambient temperature unless otherwise specified, Resistive or inductive load, 60HZ.

For Capacitive load derate current by 20%

Parameter	Symbol	MSB25J	MSB25K	MSB25M	unit
Maximum repetitive peak reverse voltage	VRRM	600	800	1000	V
Maximum RMS bridge input voltage	VRMS	420	560	700	V
Maximum DC blocking voltage	VDC	600	800	1000	V
Maximum average forward rectified output current at TA=40°C	IF(AV)		2.5		A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	IFSM		60		A
Reverse rectified time IF=0.5A IR=1A IRR=0.25A	Trr		10		μs
Rating for fusing(t<8.3ms)	I ² t		23		A ² sec
Typical thermal resistance per element(1)	ReJA		110		°C/w
Typical thermal resistance per element(2)	C _j		25.0		pF
Operating junction and storage temperature range	T _J , T _{STG}		-55 to +150		°C

Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified, Resistive or inductive load, 60HZ.






For Capacitive load derate current by 20%

Parameter	Symbol	MSB25J	MSB25K	MSB25M	unit
Maximum instantaneous forward voltage drop per leg at 1.25A	VF		1.0		V
Maximum DC reverse current at ratde TA=25°C DC blocking voltage per element TA=125°C	IR		-55to+150 -55to+150		µ A

Notes:(1)Thermal resistance from Junction to Ambent on P.C.board mounting.

(2)Measured at 1.0MHz and applied reverse voltage of 4.0 volts.


Rating and Characteristic Curves (TA=25°C Unless otherwise noted)



Ordering Information(Example)

PREFREN P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MSB25J~MSB25M	Approximate 0.20	3000	6000	36000	REEL

Suggested pad layout



Unit:mm	
DIM	MIN
P0	5.12
P1	8.73
L	1.2
W	2.22

Dimensions in millimeters